

# 2MB-54IR42L210 Series

## WEATHER PROOF INFRARED CAMERA



### FEATURES

- Weather Proof IR Camera
- SONY / SHARP Color CCD
- IR LED: 5 x 42Pcs / IR Distance: 40M
- Water Resistance: IP-66
- Built-in Bracket, 3-Axis Direction Bracket
- Auto White Balance (AWB)
- Lens: 2.8-10mm Varifocal Lens
- Dimension:  
140mm (W) x 83mm (H) x 80mm (D)

ITEM	2MB-42IR42L210	2MB-42SIR42L210	2MB-52IR42L210	2MB-54IR42L210
<b>Image Sensor</b>	1/3" SONY	1/4" SHARP	1/3" SONY	1/3" SONY
<b>Horizontal Resolution</b>	420 TV Lines	420 TV Lines	520 TV Lines	540 TV Lines
<b>Pixels</b>	PAL: 500 (H) x 582 (V) NTSC: 510 (H) x 492 (V)	PAL: 500 (H) x 582 (V) NTSC: 510 (H) x 492 (V)	PAL: 752 (H) x 582 (V) NTSC: 768 (H) x 494 (V)	PAL: 795 (H) x 596 (V) NTSC: 811 (H) x 508 (V)
<b>TV System</b>	PAL / NTSC			
<b>IR LED</b>	5 x 42 Pcs			
<b>IR Series Distance</b>	40M			
<b>Lens</b>	2.8-10mm Varifocal Lens			
<b>Sync System</b>	Internal			
<b>IR Status</b>	Under 10 Lux By CDS			
<b>Usable Illumination</b>	0 Lux / F2.0 (LED On)			
<b>IR Power On</b>	CDS Auto Control			
<b>S/N Ratio</b>	≥48 dB (AGC Off)			
<b>Gamma Correction</b>	0.45			
<b>Video Out</b>	Composite Signal (1.0 Vp-p, 75Ω)			
<b>Scanning System</b>	PAL: 625 Lines, 50 Field / sec. NTSC: 525 Lines, 60 Field / sec.			
<b>Electronic Shutter Time</b>	Auto: PAL: 1/50-1/100,000 sec. NTSC: 1/60-1/100,000 sec.			
<b>Operation Temperature</b>	-10°C ~ +50°C / RH95% Max			
<b>Storage Temperature</b>	-20°C ~ +60°C / RH95% Max			
<b>White Balance</b>	Auto			
<b>Power Source</b>	12VDC / 300mA			
<b>Dimension</b>	140mm (W) x 83mm (H) x 80mm (D)			
<b>Weight</b>	1300g			

